



PRODUCTS CATALOG 2024

IT'S EASY.

IT'S EASY.



CAR COSMETICS

Cockpit spray



This spray cleans, polishes and protects all plastic, leather, wooden and leatherette parts in the interior of a vehicle. It has an anti-static effect and protects the material against brittleness.

VOLUME: 400 ml
PCS IN A CARTON: 6

CODE:
CY-1031260007 Lemon
CY-1031260009 Vanilla
CY-1031260013 Forest fruits
CY-1031260011 Orange
CY-1031260008 Apple
CY-502332 Watermelon

Cockpit Spray Matt Effect



The Cockpit spray matt effect leaves a dull finish.

VOLUME: 400 ml
PCS IN A CARTON: 6

CODE: CY-1031260012

Cockpit Cleaner




The cleaner perfectly removes grease and dirt from the plastic surfaces in car interiors. The cleaned surface is left clean and degreased.

VOLUME: 300 ml
PCS IN A CARTON: 10

CODE: CY-1031370002

Active Foam Glass Cleaner



The cleaner perfectly removes grease and dirt from car glass. The cleaned surface is left crystal clear. The product is also suitable for cleaning mirrors.

VOLUME: 300 ml
PCS IN A CARTON: 10

CODE: CY-1031370001

CAR COSMETICS



Textile Cleaner



The cleaner perfectly removes dirt from textile upholstery of seats, car carpets and textile accessories in the vehicle and in the home.

VOLUME: 300 ml
PCS IN A CARTON: 10

CODE: CY-1031370003

Glass + Mirror Wipes



For quick and easy cleaning of car windows and mirrors in a practical package.

VOLUME: 30 ks
PCS IN A CARTON: 8

CODE: CY-9031216004

Hand wipes



Quick cleaning of dirty hands without the use of water, for example after repairing a flat tire or refuelling. Easy to use and practical packaging in the passenger compartment.

VOLUME: 30 ks
PCS IN A CARTON: 8

CODE: CY-9031216005

Cockpit Wipes



Cockpit wipes are used for quick cleaning of car interiors. The scent of lemon, orange and vanilla in a practical and compact package.

VOLUME: 30 ks
PCS IN A CARTON: 8

CY-9031216003 Lemon
CY-9031216011 Vanilla
CY-9031216012 Orange

Car Shampoo



This product is intended for washing and cleaning all types of motor vehicle paintwork and all painted surfaces. Perfumed.

VOLUME: 500 ml / 25 l
PCS IN A CARTON: 10 / 1

CODE: CY-1031380004 /
/ CY-1031386007

Wax Car Shampoo



This shampoo washes and polishes your car in one operation. It ensures the gloss and preservation of the paintwork due to its wax content and is designed for all types of paints and painted surfaces of cars. Perfumed.

VOLUME: 500 ml
PCS IN A CARTON: 10

CODE: CY-8031210003

Old Paint Polish



This product is suitable for cleaning and polishing old paint. It contains a fine abrasive that removes the oxidized layer of the paint and dirt and renews the original colour and gloss of old paints. The product will create a protective hydrophobic film.

VOLUME: 250 ml
PCS IN A CARTON: 10

CODE: CY-8031210001

New and Metallic Paint Polish



This product is suitable for polishing quickly new well-maintained paintwork. It contains a special blend of oils that protects the paintwork against external influences.

VOLUME: 250 ml
PCS IN A CARTON: 10

CODE: CY-8031210002

Antibacterial upholstery and plastic cleaner



Cleans and disinfects car upholstery and interior plastics. Neutralises unpleasant odours. Perfumed with the scent of lemon. Disinfectant and antibacterial effects.

VOLUME: 500 ml
PCS IN A CARTON: 12

CODE: CY-506101

Glass and plastic cleaner



A unique product that simply and perfectly cleans both the windows and the interior and exterior plastics of your car. Specially developed for cleaning all glass surfaces of the car, polycarbonate lights, dashboards and all interior plastics. Suitable for both soft and hard plastics.

VOLUME: 650 ml
PCS IN A CARTON: 12

CODE: CY-506118

Engine Cleaner



A highly effective product designed for cleaning car engines and other mechanical components. Apply the product with a pump spray to the areas to be cleaned, let it act for 5-10 minutes, and then rinse the cleaned areas with clean water.

VOLUME: 500 ml / 5 l
PCS IN A CARTON: 12 / 4

CODE: CY-001086 / CY-504312

Insect Remover



A concentrated product that helps to remove effectively all insect remains from windscreens, grilles, reflectors, and car bodies. It does not have an aggressive effect on paintwork. Perfumed.

VOLUME: 500 ml
PCS IN A CARTON: 12

CODE: CY-754180

Wheel Cleaner



Disc cleaner effectively removes dirt from brake pads, tar, salt and mud. It restores the original shine and prevents discolouration caused by brake pad sludge. Acid-free. Safe for all types of discs.

VOLUME: 500 ml
PCS IN A CARTON: 12

CODE: CY-002670

Wheel Cleaner RED



A special cleaner with a new combination of active ingredients. It contains substances which turn red when actively applied to impurities. At the same time, redness indicates the best time to wash the product. It is designed for cleaning cast and steel rims. Easily removes dirt, such as oil residues, soot, rubber, street dirt, and dust caused by brake pads. After cleaning, the rims regain their former brilliance.

VOLUME: 500 ml
PCS IN A CARTON: 12

CODE: CY-878426

Window Cleaner



Universal cleaner for cleaning windows, mirrors, headlights and indicator lights. Quickly and effectively removes organic dirt, mud, grease, insects. Does not leave streaks. Perfectly removes dust while reducing fogging. Use. Leave on for 20 seconds. Wipe dry.

VOLUME: 650 ml
PCS IN A CARTON: 12

CODE: CY-502240

Tyre and Plastic vitalizer



A product designed to care for tyres and outer plastics and all rubber parts. It cleans, renews the original appearance, and keeps the area to which it has been applied in the elastic state. Perfumed.

VOLUME: 400 ml
PCS IN A CARTON: 10

CODE: CY-1031210006

Tyre Foam



The tyre foam contains an emulsified silicone component that adheres to the tyre surface and, thanks to a different electrical charge, it displaces the dirt which, together with the excess foam runs off. Active Anti Dirt System: the emulsified silicone component remains on the tire surface and helps the treated surfaces to resist dirt again. At the same time, it gives the tyre the desired shine.

VOLUME: 400 ml **CODE:** CY-2042210001
PCS IN A CARTON: 10

Tyre Repair



Allows you to repair a flat tire immediately - at night, in the dark, in the rain or on the motorway. Without changing the wheel or tyre. It is suitable for all types of tyres 165 x 14 and larger.

VOLUME: 500 ml **CODE:** CY-878273
PCS IN A CARTON: 6

Brake Cleaner



Use for drum and disc brakes, brake linings, drums, wheels, discs, brake components in general, clutch linings and pressure plates, and clutch components in general.

VOLUME: 600 ml **CODE:** CY-510856
PCS IN A CARTON: 12

Brake cleaner liquid



Is a quick-drying product intended for degreasing brake discs, clutch plates and other metal parts. Very effectively, safely and accurately removes brake dust, oil, silicone, grease and other impurities. For all brake system components including drums, clamps, discs, pads and cylinders. Cleaning and degreasing of general purpose parts.

VOLUME: **CODE:** CY-510986
PCS IN A CARTON:

Asphalt Remover



The product perfectly removes asphalt, bitumen, tar, oil, etc. from the body. It removes also label adhesive.

VOLUME: 300 ml **CODE:** CY-1031370004
PCS IN A CARTON: 10

Liquid Radiator Sealer



The product prevents the creation of leaks and seals small leaks in the cooling system. It has no disturbing influence on the cooling effect. The sealer contains a corrosion inhibitor. It is suitable for the cooling system of all passenger cars. The product does not damage hoses and parts made of aluminium or other metals.

VOLUME: 250 ml **CODE:** CY-878013
PCS IN A CARTON: 15

Water Removal



Makes it easy to start the engine at low temperatures. Removes moisture from the fuel system, prevents the formation of ice in the fuel. Protects the system against clogging. Miscible with petrol and diesel.

VOLUME:250 ml **CODE:** CY-877481
PCS IN A CARTON: 20

Lock De-Icer



Designed to defrost car door locks.

VOLUME: 50 ml **CODE:** CY-309880
PCS IN A CARTON: 35

Rubber stick



Prevents freezing of rubber seals, especially on doors. It gives them flexibility, prevents cracking, preserves and prolongs the lifetime period. Suitable for sealing doors of cars, boats and caravans and for household use (windows, freezers, etc.). It does not contain silicone. Apply lightly on dry rubber and spread with a soft cloth. Apply regularly.

VOLUME: 40 gr **CODE:** CY-506156
PCS IN A CARTON: 24

De-Icer



A product used for defrosting glass, headlights, and locks of vehicles.

VOLUME: 650 ml **CODE:** CY-503391
PCS IN A CARTON: 12

Glykosol Window Defroster with Scraper



A product used for defrosting glass, headlights, and locks of vehicles. It can also be used preventively.

VOLUME: 300 ml **CODE:** CY-1031270002
PCS IN A CARTON: 10

Glass Demister



The Coyote Glass Demister is a product suitable for surfaces where we want to prevent misting-up. The product is particularly suitable for use in cars and at home. Application will ensure the clear transparency of the glass and the clean reflection and mist free surface of the mirrors.

VOLUME: 500 ml **CODE:** CY-010460
PCS IN A CARTON: 12

Anti-Mist Cloth



Prevents fogging of car windows and mirrors. It can also be used in households and in places with increased instantaneous humidity (e.g. in bathrooms).

VOLUME: 1 **CODE:** CY-1750303
PCS IN A CARTON: 128

Rain Off



The spray, also called liquid wipers, forms a protective film on glass surfaces, which effectively repels raindrops and increases visibility in bad weather.

VOLUME: 500 ml **CODE:** CY-512416
PCS IN A CARTON: 12

Super start



Super start is an ethereal solution for starting an engine. It works in any weather, even at temperatures down to -50 °C. It contains special lubricants that protect the engine at the critical start time. Recommended for petrol engines, diesel engines, motorcycles, mowers, saws, etc.

VOLUME: 400 ml **CODE:** CY-503407
PCS IN A CARTON: 24

Polishing cloth



Versatile polishing cloth made of fine microfibre, without seams and edges that could scratch the bodywork. It can be used to remove wax residues after polishing, or to wipe dust and wash windows. Size 40 x 40 cm.

PCS IN A CARTON: 100 **CODE:** CY-509300

IT'S EASY.



OILS AND LUBRICANTS



OILS AND LUBRICANTS

0W-20



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-511679

0W-20 is a fully synthetic Mid SAPS engine oil for passenger cars with gasoline and diesel engines. It is compatible with the latest diesel particulate filters (DPF) and petrol catalytic converters. Provides excellent wear protection throughout the interval between oil changes.

Field of application:

This high-performance oil with carefully selected ingredients is perfectly suited for the application of specifications in VW cars after 508 00 and 509 00. COYOTE LUBES 0W-20 is the latest engine oil development with low viscosity for the efficiency of emission systems in modern diesel and gasoline engines that require viscosity class SAE 0W-20.

Features:

- Lower fuel consumption.
- Reduction of the formation of combustion residues (Mid SAPS).
- Excellent cold start behavior.
- Excellent shear stability at high temperatures.
- Extended oil change intervals.
- Very good cleaning ability and dispersion.
- Very strong protection against wear, corrosion and foaming.
- Dark green color.

MEETS THE STANDARDS:

VW 508 00 / 509 00,
Porsche C20 ,
Ford WSS-M2C956-A1,
ACEA C5, API SN,
API SN Plus

0W-30 C2/C3



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-511655

0W-30 C2/C3 is a synthetic high-performance Low SAPS engine oil for passenger cars with gasoline and diesel engines with a particulate filter.

Field of application:

It minimizes wear and improves fuel economy, as well as facilitating cold engine starts. Extends the life of the diesel particulate filter (DPF) by reducing the concentration of ash-forming particles in the exhaust gas. Thanks to its composition with special base oils, it achieves a high viscosity index and provides long-term engine protection.

Features:

- Very good wear protection.
- Improved corrosion protection.
- Protection against sludge formation.
- Promotes fuel economy.
- Good properties at low temperatures.

MEETS THE STANDARDS:

ACEA C2/C3, API SN,
VW 504.00/507.00,
MB 229.31/229.51/229.52,
BMW Longlife-04,
Fiat 9.55535-DS1,
Fiat 9.55535-GS1,
Porsche C30

5W-30



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507115

VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-507955

Innovative motor oil based on base oils produced by HC synthesis for all passenger cars. Does not contain heavy metals and at the same time offers maximum performance. Suitable for vehicles with additional exhaust gas treatment systems such as particulate filters or catalytic converters. Can also be used in engines of older vehicles without regardless of the emission class. It forms almost no deposits in the exhaust gas turbocharger, so that the charging pressure remains optimal for a long time. The thermal stability and lower sulphated ash content guarantee particularly good piston cleanliness regardless of the fuel.

Field of application:

It meets the engine oil requirements for vehicles with the most modern exhaust gas aftertreatment systems. It can be used in diesel, petrol and gas engine vehicles and is miscible with other motor oils..

Features:

- Excellent protection against wear even under continuous load at full engine power.
- Around 3% lower fuel consumption reduces emissions of harmful substances.
- Low oil consumption due to very low evaporation losses.

MEETS THE STANDARDS:

ACEA C3
API SN/SM/CF
VW 502.00/505.00/505.01
MB 229.51
BMW Longlife-04

5W-30 Longlife III



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507177

VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-507771

Coyote Lubes 5W-30 Longlife III is made with the most modern technology, which ensures maximum compatibility with exhaust gas treatment devices. It helps to keep the particulate filter clean, thus maintaining engine performance. It reduces friction in the engine and thus allows achieving fuel economy.

Field of application:

It can be used in modern gasoline engines, diesel engines with particulate filters and gas engines.

Features:

- Very stable and excellent viscosity properties.
- Very good cold start properties.
- Low friction losses.
- Optimal wear protection.
- Low emissions and evaporative loss of engine oil.

MEETS THE STANDARDS:

API SN
ACEA C3
VW 504.00/507.00
MB 229.31/229.51

5W-40



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507085

VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-507894

Highly alloyed semi-synthetic light-speed multi-grade motor oil. Carefully selected, highly effective additives give this top-of-the-line motor oil excellent properties.

Field of application:

Ideal for modern petrol and diesel engines of passenger cars and vans with and without a turbocharger.

Features:

- Very stable and excellent viscosity properties.
- Very good cold start properties.
- Low friction losses. Optimal wear protection.
- Low emissions and evaporative loss of engine oil.

MEETS THE STANDARDS:

API SM/CF
ACEA A3/B4
VW 502.00/505.00
Renault RN 0700/0710
Porsche A40
BMW Longlife-01
GM-LL-B-025
MB 229.3

5W-40 Racing



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507139

Semi-synthetic motor oil for year-round use. It is based on modern synthetic oils with a carefully selected package of the highest quality refining additives. This increases the life of the oil and at the same time protects the engine against wear. Excellent low-temperature properties guarantee fuel economy and reduced exhaust gas emissions.

Field of application:

Designed for the lubrication of modern, highly loaded gasoline and diesel engines (including turbocharged ones) of passenger cars and light commercial vehicles with the highest requirements for oil performance in year-round operation. It is recommended for sports and competition car engines. A particularly advantageous application is in engines operating at very low temperatures and where fuel economy is required. It is also suitable for gas engines.

Features:

- It limits the formation of high-temperature deposits and low-temperature sludge.
- Excellent engine protection against corrosion and wear.
- Good startability even at low temperatures.
- Maximum use of replacement periods recommended by the engine manufacturer.
- Reduction of operating costs due to reduction of passive resistance of the motor.

MEETS THE STANDARDS:

API SM/CF; ACEA A3/B4;
VW 502.00/505.00
Renault RN 0700/0710;
Porsche A40
BMW Longlife-01;
GM-LL-B-025
MB 229.3

5W-40 PD LA



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507276

Fully synthetic engine oil designed for year-round use. It contains modern synthetic base oils and a carefully selected package of the highest quality refining additives. It is especially suitable for vehicles with exhaust gas aftertreatment systems such as particulate filters or catalytic converters. Can also be used in older vehicle engines regardless of emission class. Thermal stability and lower sulphated ash content guarantee particularly good piston cleanliness and almost no deposits in the turbocharger.

Field of application:

Designed for lubrication of modern, highly loaded gasoline and diesel engines (including turbocharged) of passenger cars and light commercial vehicles with the highest oil performance requirements in year-round operation, including engines with a pump-nozzle injection system. The application is particularly advantageous in engines operating at very low temperatures and where fuel economy is required. Also suitable for gas engines.

Features:

- Restriction of the formation of high-temperature deposits and low-temperature sludge.
- Excellent protection of the engine against corrosion and wear.
- Good startability even at very low temperatures.
- Maximum use of replacement periods recommended by the engine manufacturer.
- Reduction of passive engine resistances.
- High thermal stability, usable for turbo.

MEETS THE STANDARDS:

ACEA C3; API SN/SM/CF;
SAE 5W-40;
VW 502.00/505.00/505.01;
Renault RN 0700/0710;
Porsche A40;
Ford WSS M2C 917A;
GM Dexos 2;
MB 229.31

10W-40



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507047

VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-507757

Coyote Lubes 10W-40 increases engine performance while protecting it against harmful deposits and abrasion thanks to its advanced formulation. Suitable for use in a wide range of vehicles operated in everyday driving mode.

Field of application:

It can be used in petrol, diesel and gas engines. It is also suitable for engines using bio-diesel or gasoline/ethanol mixture as fuel.

Features:

- Actively removes harmful performance-reducing deposits.
- Helps remove sludge from previous oils.
- Protects the engine from wear and tear and during the entire service interval.
- Lower oil consumption due to lower evaporation.

MEETS THE STANDARDS:

API SN/SM
ACEA A3/B3/B4
VW 500.00/501.01/
505.00
MB 229.1/229.3
Renault RN 0700

10W-40 Extreme



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507153

VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-507764

Synthetic-based engine oil. Prevents the formation of deposits and sludge in the engine, thus ensuring its cleanliness and efficient operation. Suitable for use in a wide range of modern vehicles operated in demanding conditions.

Field of application:

It can be used in gasoline, diesel (without particulate filter) and gas engines. Also suitable for engines using bio-diesel or gasoline/ethanol mixture as fuel. It protects the engines of modern vehicles in demanding conditions of daily operation and thus helps to extend their service life.

Features:

- Actively removes harmful performance-reducing deposits.
- Helps remove sludge from previous oils.
- Protects the engine from wear and tear, prolongs its life even in daily use.
- Protects the engine during the entire service interval.
- Faster oil flow for faster engine warm-up.
- Lower oil consumption.

MEETS THE STANDARDS:

API SL/SN/CF
ACEA A3/B3/B4
VW 500.00/501.01/
502.00/505.00
MB 229.1/229.3
Renault RN 0700
Fiat 9.55535-G2
Jaso SG+

10W-40 Plus



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507283

Universal motor oil for vehicles with extended drain intervals and for mixed fleets, among others. Offers increased wear protection even under extreme loads. Helps reduce operating costs by reducing fuel and oil consumption compared to conventional motor oils.

Field of application:

It is ideal for use in mixed fleets. Can be used in all commercial and construction vehicles, including turbocharged vehicles, as well as turbocharged and non-turbocharged gasoline and diesel passenger cars. Suitable for a mixed fleet, where it simplifies the use of types and prevents unwanted confusion. It can also be used for railway and marine diesel engines operating at low speeds and high loads.

Features:

- It ensures easy starting even in extreme cold.
- Reduces downtime, operating costs and environmental impact.
- Allows to reduce the number of lubricating oils. It is stable at high temperatures and does not form deposits.
- Long-term favorable properties even with high shear loads.
- High alkaline reserve. It protects against the formation of deposits and keeps the engine cylinders clean.

MEETS THE STANDARDS:

API SL/SN/CF;
ACEA A3/B3/B4
VW 500.00/501.01/
502.00/505.00;
MB 229.1/229.3
Renault RN 0700; Fiat
9.55535-G2; Jaso SG+

15W-40



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507306
VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-509737

Motor oil from highly refined petroleum base oils and a balanced additive package that ensures modern performance levels.

Field of application:

Year-round use in highly stressed turbocharged and non-supercharged diesel engines of trucks, construction machinery and buses. Suitable for use in passenger cars and light vans with diesel or gasoline engines that operate in severe operating conditions.

Features:

- It protects against the formation of deposits and keeps the engine cylinders clean.
- Long-term favorable properties even with high shear loads.
- It maintains good viscosity properties during the entire oil change interval.
- High alkaline reserve.
- Lower sediment formation at high temperatures

MEETS THE STANDARDS:

SAE 15W-40
API SG/CF-4

15W-40 GX



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507245

Year-round multi-grade motor oil based on extremely high-quality base oils. Together with a newly developed combination of additives, this high-quality motor oil has excellent properties.

Field of application:

Ideal for year-round use in all turbocharged and non-supercharged petrol and diesel engines.

Features:

- Protects against wear, corrosion and deposits.
- Prevents the formation of black sludge in the oil.
- Suitable for use with catalysts.
- For turbocharged engines, it stabilizes their performance.

MEETS THE STANDARDS:

ACEA A3/B4
API SL/CG-4
VW 501.01/505.00
MB 229.1

M6A



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507108

Is a summer motor oil made from petroleum base oil and additives to improve antioxidant, detergent and dispersing properties.

Field of application:

It is intended for lubrication of undemanding older types of gasoline and diesel engines operating in moderate operating conditions.

Features:

- For engines with low oil performance requirements.
- Especially for summer operation of gasoline engines.
- Protection against the formation of oxidation products.

MEETS THE STANDARDS:

API SB/CB
SAE 30

M6AD



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507160
VOLUME: 5 l
CODE: CY-507887
PCS IN A CARTON: 4

Summer motor oil made from petroleum base oil and additives to improve antioxidant, detergent and dispersing properties.

Field of application:

It is intended for lubrication of undemanding older types of gasoline and non-supercharged diesel engines operating in mild operating conditions.

Features:

- For engines with low oil performance requirements.
- For summer operation of petrol and diesel engines.
- Protection against the formation of oxidation products.

MEETS THE STANDARDS:

API SC/CB
SAE 30

2T



VOLUME: 100 ml
PCS IN A CARTON: 30
CODE: CY-507054

VOLUME: 500 ml
PCS IN A CARTON: 20
CODE: CY-507078

VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507313

Modern mineral oil for the lubrication of two-stroke gasoline engines. It contains highly refined oils with refining additives that modify the lubricating properties of the product and prevent the formation of deposits on the electrodes of candles, cylinder walls and exhaust channels. It is not recommended to use in a mixture that lubricates two-stroke engines working with fuels containing bioethanol (E85).

Field of application:

For the lubrication of heavily loaded two-stroke gasoline engines lubricated with a greasy mixture, such as engines of motorcycles, cars, scooters, chainsaws, pumps and other engines used in garden tools.

Features:

- Perfectly miscible with fuel.
- Reduction of smoke and harmful emissions from the engine.
- It ensures constant cleanliness of the piston and combustion chamber and free movement of the piston rings.

MEETS THE STANDARDS:

API TC
SAE 40
JASO FC

2T Garden



VOLUME: 250 ml
PCS IN A CARTON: 20
CODE: CY-508792

VOLUME: 500 ml
PCS IN A CARTON: 20
CODE: CY-508815

Synthetic two-stroke engine oil from highly refined base oils and high-performance additives for use in small garden machinery. Exceeds motor oil specifications issued by small garden machinery manufacturers such as MTD, Briggs & Stratton, Honda and Tecumseh. Not recommended for two-stroke engines lubricated mixtures working with fuels containing bioethanol (E85).

Field of application:

Designed for two-stroke engines of small garden equipment, such as lawn mowers, brush cutters, hand-held chainsaws, electric generators, rotavators, etc.

Features:

- Perfectly miscible with fuel.
- Reduction of smoke and harmful emissions from the engine.
- It ensures constant cleanliness of the piston and combustion chamber and the free movement of the piston rings-

MEETS THE STANDARDS:

API TC+
JASO FD
CEC TSC-3
ISO-L-EGD

VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507207

Garden



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507146

High-quality seasonal mineral oil intended for use in small agricultural and garden equipment equipped with four-stroke engines. The quality of the oil is guaranteed by an appropriately selected production technology based on deeply refined mineral base oils and carefully selected refining additives.

Field of application:

Mineral engine oil intended for the lubrication of small agricultural and garden machinery equipped with four-stroke engines (e.g. mowers, garden tractors, cultivators, plows, cutters).

Features:

- Maintains a permanent lubricating film under conditions of high thermal and mechanical load.
- Lower oil consumption, thanks to lower evaporation.
- Very good antioxidant properties preventing the formation of so-called black sludge.
- Prevents corrosion and the formation of high-temperature deposits.
- Fully miscible with other oils of the same viscosity and performance class.

MEETS THE STANDARDS:

API SG/CD
SAE 10W-30

4T Garden



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507221

Special motor oil from synthetic base oils using a complex additive system that ensures the highest performance level and good viscosity characteristics for use in small garden machines. Exceeds the motor oil specifications prescribed by manufacturers of small garden machines such as MTD, Briggs & Stratton, Honda and Tecumseh.

Field of application:

Designed for four-stroke engines of small garden equipment, electric generators and snow blower engines.

Features:

- Easy starting even in cold weather.
- Stable lubricating films with high load-bearing capacity and protection against wear even under heavy loads.
- Maintains good lubricity during a long drain interval.
- It resists aging processes for a long time and does not form harmful deposits.

MEETS THE STANDARDS:

ACEA A3/B4
API SL/CF
SAE 10W-30

Garden Bio



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507214

A sticky oil made from high-quality, low-aromatic base oil with a selected combination of additives. It is specially developed for lubricating the chain and guide rails of modern chainsaws. Due to its good properties at lower temperatures, it is also suitable for work in winter. It is not suitable for engine lubrication (mixing with fuel).

Field of application:

Can be used in manual or machine chainsaws according to manufacturer's specifications. Suitable for the lubrication of chains, slideways and guides in industrial applications that require a lubricant with good adhesion, corrosion and wear protection and a low pour point.

Features:

- Holds well on guide bars and saw chains and ensures their optimal service life.
- Reduces maintenance costs.
- Flow rate even at low operating temperatures.

PP 80



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507269

Mineral automotive winter gear oil with good lubrication, anti-corrosion and anti-oxidation properties. It has high pressure transfer resistance and good foaming resistance.

Field of application:

For use in mechanical gearboxes and transmissions (except hypoid) of cars, agricultural machinery and mobile equipment that operate at low ambient temperatures. Furthermore, in equipment and oil-lubricated rolling bearings, where API GL-4 grade oil can be used.

Features:

- Gear wear protection.
- Long life of synchronous rings thanks to additives improving EP properties.
- Low foaming tendency.
- Long-term preservation of properties.
- Excellent corrosion protection.

MEETS THE STANDARDS:

API GL-4
SAE 80W

PP 90



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507290

Mineral automotive summer gear oil with good lubrication, anti-corrosion and anti-oxidation properties. It has high pressure transfer resistance and good foaming resistance.

Field of application:

For use in mechanical gearboxes and transmissions (except hypoid) of cars, agricultural machinery and mobile equipment that operate at low ambient temperatures. Furthermore, in equipment and oil-lubricated rolling bearings, where API GL-4 grade oil can be used.

Features:

- Gear wear protection.
- Long life of synchronous rings thanks to additives improving EP properties.
- Low foaming tendency.
- Long-term preservation of properties.
- Excellent corrosion protection.

MEETS THE STANDARDS:

API GL-4
SAE 90

PP 90 H



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-511693

A mineral automotive transmission oil that has very good lubrication, anti-corrosion and anti-oxidation properties, high transfer resistance and good foaming resistance.

Field of application:

It is intended for use in mechanical transmissions and transmissions (especially hypoid) of cars, mobile equipment and agricultural machinery operating under severe operating conditions, i.e. high speeds, sudden load changes and high torque. Furthermore, it is intended for use in various machines and equipment, where the manufacturer recommends the use of API GL-5 oil.

Features:

- Long life of synchronous rings thanks to additives improving EP properties.
- Low foaming tendency.
- Long-term preservation of properties.
- Excellent corrosion protection.

MEETS THE STANDARDS:

SAE 90,
API GL-5,
MIL-L-2105D

Dexron II D



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507252

Transmission oil for automatic transmissions of cars, trucks and buses according to Dexron II D. Thanks to the combination of oils and additives, it provides the required friction and other properties necessary for the operation of the automatic transmission.

Field of application:

Gear oil for automatic car transmissions and car accessories such as power steering, fluid clutches and hydraulics.

Features:

- High operational reliability and low wear.
- Excellent anti-corrosion properties.
- Good resistance to foaming.
- Excellent compatibility due to the sealing materials used.

MEETS THE STANDARDS:

GM Dexron IID, Allison C3/C4
ZF TE-ML 03D 04D,
11A, 14A, 17C, 05L
VOITH 55:6335, xx
MAN 339 typ Z-1

Dexron III H



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-511716

DEXRON III H is suitable for use in automatic transmissions, hydraulic boosters, converters and power transmissions where ATF Dexron III H (or lower) is required.

Field of application:

Gear oil for automatic car transmissions and car auxiliary equipment such as power steering, fluid clutches and hydraulics.

Features:

- High operational reliability and low wear.
- Excellent anti-corrosion properties.
- Good resistance to foaming.

MEETS THE STANDARDS:

GM Dexron III H, Ford Mercon,
MB-Freigabe 236.1, MAN 339 Typ Z1, MAN 339
Typ V1, MAN 339 Typ L 1,
ZF TE-ML 04D/14A, Voith H55.6335.XX (G
607), Volvo 97341, Caterpillar TO-2, Allison
C-4, Allison TES 389

OTHP3



VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-507184

Universal hydraulic fluid from deeply refined base oils with additives to reduce wear. Reliable performance for a wide range of industrial and mobile hydraulic equipment. Used primarily in hydraulic systems with hydrostatic drives where thermal stress may occur.

Field of application:

Coyote Lubes OTHP3 properties exceed the requirements for HLP hydraulic oils according to DIN 51 524 part 2. It can also be used as a transmission and circulation oil.

Features:

- Does not attack common sealing materials.
- Contributes to the longer life of the device.
- Low deposit formation, long oil change intervals.
- Good water separability.
- Lower risk of cavitation.
- Good corrosion protection.

MEETS

THE STANDARDS:

ISO VG 32
ISO 1 158
DIN 51524 část 2

IT'S EASY.



SPECIAL LUBRICANTS





SPECIAL LUBRICANTS

Contact Plus



This product cleans and protects contacts against corrosion. It removes undesirably high contact resistances. It is also suitable for high and low frequency devices and for TV sets, radios, measuring instruments, and car electrical equipment.

VOLUME: 150 ml
PCS IN A CARTON: 10
CODE: CY-1031200006

Silkal 93



An ideal lubricant for bearings, pins, electrical and starting devices, locks, bicycles, and ski bindings. It cares for door seals, cooling system hoses, and rubber mouldings. A perfect separator when moulding and casting plastics, resins, and rubber products. Hydrophobic.

VOLUME: 200 ml
PCS IN A CARTON: 10
CODE: CY-1031200008

VOLUME: 400 ml
PCS IN A CARTON: 10
CODE: CY-1031200010

VOLUME: 300 ml
PCS IN A CARTON: 10
CODE: CY-1031200009

VOLUME: 5 l
PCS IN A CARTON: 1
CODE: CY-1031206000

Konkor 101



The product creates a film of oil on the preserved objects that lubricates and perfectly protects ferrous and non-ferrous metals such as steel, cast iron, copper, zinc, and lead. It is suitable for lubricating machines, instruments, engines, spare parts, accumulator battery contacts, and hinges. The product releases stuck mechanisms. It is suitable for cleaning and preserving weapons. It protects ferrous metals against corrosion.

VOLUME: 200 ml
PCS IN A CARTON: 10
CODE: CY-1031200001

VOLUME: 400 ml
PCS IN A CARTON: 10
CODE: CY-1031200003

VOLUME: 300 ml
PCS IN A CARTON: 10
CODE: CY-1031200002

Lithium Grease



A multi-purpose mineral lubricating grease thickened with lithium soap and containing additives providing resistance to extreme pressures. Suitable for all types of bearings and mechanisms operating at high loads and temperatures. It is also excellently resistant to water and humidity. Provides a high level of protection against corrosion in systems with aggressive conditions. Provides long-lasting lubrication. It does not drip after application. Reduces friction, especially in the metal to metal system.

VOLUME: 400 ml
PCS IN A CARTON: 12
CODE: CY-513260

GRAFIT-SPRAY



It forms a protective film that ensures a long-lasting lubricating effect. Application on: hinges, rails, shafts, locks, winches, nuts, ball joints, leave springs, and more.

VOLUME: 400 ml
PCS IN A CARTON: 12
CODE: CY-879850

PTFE SPRAY



A high-quality lubricant for the treatment of metal and plastic mechanical parts. Application: for chains, gear wheels, rails, door hinges, sliding doors, vacuum pumps, conveyors, clamping mechanisms, ratchets, rubber seals, and others.

VOLUME: 400 ml
PCS IN A CARTON: 12
CODE: CY-8798051

IT'S EASY.



PLASTIC LUBRICANTS



PLASTIC LUBRICANTS

A 00



VOLUME: 250 g
PCS IN A CARTON: 24
CODE: CY-508877

Plastic lubricant based on high quality petroleum base oil strengthened with complex aluminum soap. The grease is used to lubricate sliding bearings, especially the chassis of mobile machines and equipment. It is also used to lubricate vertical and ball joints and other sliding bearings (shaft bearings, tie rod bearings, turntables, etc.) of cars and mobile machines. The grease can also be used to lubricate older, slow-moving, closed or leaky gearboxes. The recommended operating temperature is from -20 °C to 140 °C.

MEETS THE STANDARDS:

- DIN 51 502: GP00N-20
- ISO 6743-9: L-X BDHB 00

LA 2



VOLUME: 250 g
PCS IN A CARTON: 24
CODE: CY-508853

Plastic lubricant with a short-fibre structure, semi-soft to medium consistency based on a high quality petroleum base oil fortified with lithium soap. It is enhanced with inhibitors. It is used to lubricate a wide range of medium to heavy duty rolling bearings in automobiles etc. It is suitable for lubricating plain bearings, small gears and friction contacts. Water resistance - the product can be used in bearings operating in contact with water. Can be used in household applications. The recommended operating temperature is -30 °C to 120 °C.

MEETS THE STANDARDS:

- DIN 51 502: KP2K-30
- ISO 6743-9: CCEB 2

LV 2-3



VOLUME: 250 g
PCS IN A CARTON: 24
CODE: CY-508839

Plastic lubricant with a fine short fiber structure based on highly refined mineral oil strengthened with lithium soap. The plastic grease is intended for the lubrication of sliding and rolling bearings that are not exposed to high loads and operate in the temperature range from -30 to 140 °C. They are also suitable for lubricating some small gears. The choice of lubricant depends on the lubrication method of the given friction node, the speed factor and the working temperature.

MEETS THE STANDARDS:

- DIN 51 502: K3N-30
- ISO 6743-9: L-X CDEB3

IT'S EASY.

SERVICE FLUIDS



SERVICE FLUIDS

DOT3 Brake Fluid



The brake fluids are designed for brake and clutch systems of cars with the required performance levels and functional characteristics according to the relevant international and national standards and the binding regulations of the car manufacturers. Compatibility: The Coyote brake fluids can be replaced with commonly available brake fluids with the same DOT 3 specification or such brake fluids can be added to them.

VOLUME: 500 ml
PCS IN A CARTON: 12
CODE: CY-511990

VOLUME: 3 L
PCS IN A CARTON: 3
CODE: CY-512003

DOT4 Brake Fluid



The brake fluids are designed for brake and clutch systems of cars with the required performance levels and functional characteristics according to the relevant international and national standards and the binding regulations of the car manufacturers. Compatibility: The Coyote brake fluids can be replaced with commonly available brake fluids with the same DOT 4 specification or such brake fluids can be added to them.

VOLUME: 500 ml
PCS IN A CARTON: 12
CODE: CY-512010

VOLUME: 3 l
PCS IN A CARTON: 3
CODE: CY-512027

Glykosol 2 in 1 summer liquid



Screenwash with new liquid wiper technology. Improves visibility in bad weather. Removes insect residue, dust and oil. Covers the surface with a protective hydrophobic film that provides a liquid wiper effect on the glass. Does not damage paintwork, rubber or plastic parts. Spreads a refreshing fragrance. Does not freeze up to - 5 °C.

VOLUME: 4 l
PCS IN A CARTON: 3
CODE: CY-877856

Summer screenwash Kiwi-melon



VOLUME: 3 l
PCS IN A CARTON: 3
CODE: CY-879218

VOLUME: 5 l
PCS IN A CARTON: 3
CODE: CY-879225

Summer screenwash Apple



VOLUME: 3 l
PCS IN A CARTON: 3
CODE: CY-879249

VOLUME: 5 l
PCS IN A CARTON: 3
CODE: CY-879256

Summer screenwash Soft pack



Soft pack
VOLUME: 3 l
PCS IN A CARTON: 5
CODE: CY-AM77658

Summer liquid NANO



Summer mixture for car windshield washers and headlights. The mixture is made using NANOTECHNOLOGY, thanks to which the liquid has excellent cleaning properties. It reduces the adhesion of insect remains and other dirt to the glass and headlights. Does not damage polycarbonate headlights. Cleans windows more thoroughly and faster compared to ordinary liquids without nano-technology. NO DYE → PURELY TRANSPARENT

VOLUME: 2 l
PCS IN A CARTON: 4
CODE: CY-505425

VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-5054181

Winter screenwash NANO



The mixture is produced using NANO technology, thanks to which the fluid has excellent cleaning properties. Reduces sticking of insect debris and other dirt on windscreens and headlights. Does not damage polycarbonate headlights. Cleans windows more thoroughly and faster compared to conventional liquids without nanotechnology. DYE-FREE PURE CLEAR

VOLUME: 2 l
PCS IN A CARTON: 4
CODE: CY-506231

VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-5062481

Winter screenwash -20 °C Soft pack



Soft pack
VOLUME: 3 l
PCS IN A CARTON: 5
CODE: CY-AM77450

Winter screenwash -20 °C / -30 °C / -40 °C



-20 °C
VOLUME: 3 l
PCS IN A CARTON: 3
CODE: CY-4005877160

VOLUME: 5 l
PCS IN A CARTON: 3
CODE: CY-4005877177



-30 °C
VOLUME: 3 l
PCS IN A CARTON: 3
CODE: CY-4005877399

VOLUME: 5 l
PCS IN A CARTON: 3
CODE: CY-4005877405



-40 °C
VOLUME: 3 l
PCS IN A CARTON: 3
CODE: CY-4005877191

VOLUME: 5 l
PCS IN A CARTON: 3
CODE: CY-1031226007

Winter screenwash PROFI -20 °C / -40 °C / -80 °C



-20 °C
VOLUME: 20 l
CODE: CY-511594

VOLUME: 200 l
CODE: CY-511600



-40 °C
VOLUME: 20 l
CODE: CY-511617

VOLUME: 200 l
CODE: CY-511624



-80 °C
VOLUME: 20 l
CODE: CY-511631

Coolant G11 Univerzal READY -30 °C



Traditional ethylene glycol based coolant containing partially organic corrosion inhibitors including silicates. It protects the cooling system of the motor vehicle against frost and corrosion all year round. Guarantees very good heat transfer. Complies with VW TL 774 C and ASTM D 3306 standards. It is also suitable for all-aluminium engines. Can be mixed with all ethylene glycol based fluids of the same performance category. The replacement period of the product in the system is 2-3 years. The product is intended for direct use without dilution.

VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-5877542

VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-5877559

Coolant G11 Univerzal concentrate



Traditional ethylene glycol-based coolant containing partially organic corrosion inhibitors including silicates. It protects the cooling system of a motor vehicle against frost and corrosion all year round. Guarantees very good heat transfer. Complies with VW TL 774 C standards and ASTM D 3306. It is also suitable for all-aluminium engines. Can be mixed with all ethylene glycol based fluids of the same performance category. The replacement period of the product in the system is 2-3 years. The product is concentrated and diluted according to the instructions before use.

VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-5733116

VOLUME: 60 l
PCS IN A CARTON: 12
CODE: CY-877085

VOLUME: 3 l
PCS IN A CARTON: 3
CODE: CY-1031256002

VOLUME: 200 l
PCS IN A CARTON: 1
CODE: CY-877092

VOLUME: 25 l
PCS IN A CARTON: 1
CODE: CY-877078

VOLUME: 1000 l
PCS IN A CARTON: 12
CODE: CY-877108

Coolant G12+ D/F concentrate



Modern coolant based on ethylene glycol containing organic corrosion inhibitors, without silicates. It protects the cooling system of the motor vehicle against frost and corrosion all year round. Guarantees very good heat transfer. Conforms to VW TL 774 D/F and ASTM D 3306. Can be mixed with all ethylene glycol based fluids of the same performance category. The product is concentrated and diluted according to the instructions before use

VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-5004865

VOLUME: 60 l
PCS IN A CARTON: 1
CODE: CY-877122

VOLUME: 3 l
PCS IN A CARTON: 3
CODE: CY-1031256015

VOLUME: 200 l
PCS IN A CARTON: 1
CODE: CY-877139

VOLUME: 25 l
PCS IN A CARTON: 1
CODE: CY-877115

VOLUME: 1000 l
PCS IN A CARTON: 1
CODE: CY-877146

Coolant G12 + D/F READY -30 °C



Modern coolant based on ethylene glycol containing organic corrosion inhibitors, without silicates. It protects the cooling system of the motor vehicle against frost and corrosion all year round. Guarantees very good heat transfer. Conforms to VW TL 774 D/F and ASTM D 3306. Can be mixed with all ethylene glycol based fluids of the same performance category. The product is intended for direct use without dilution.

VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-5877528

VOLUME: 5 l
PCS IN A CARTON: 4
CODE: CY-5877535

Coolant G13 READY -30°C



Modern ethylene glycol-based coolant containing organic corrosion inhibitors, including silicates. It protects the cooling system of the motor vehicle against frost and corrosion all year round. Guarantees very good heat transfer. Particularly suitable for all-aluminium engines. Meets BS 6580 (2010), ASTM D 3306, SAE J 1034, Mercedes Benz325.5, MAN324 Si-OAT, VW TL 774 type J. The product is intended for direct use without dilution.

VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-5878037

Coolant G12EVO READY -30°C



Modern coolant based on monoethylene glycol (ethane-1,2-diol) suitable for cooling circuits of all engines, especially vehicles with modern radiators and smaller engines. The product is the optimal choice for electric vehicles (BEV), including hybrid (HEV) and plug-in hybrid (PHEV) cars, as well as new vehicles with internal combustion engines. The product contains highly effective corrosion inhibitors called PSi-OAT. Corresponds to AS 2108-2004, ASTM D3306, D4985, D7583, BS 6580 (2010), CUNA NC 956-16, GG 6580 (2010), SAE J 814, J1034, Deutz DQC CC-14, JIS K 2234 (2006), PN-C-40007 (2000), ÖNORM V 5123 (2009), SANS 1251 (2005), and VW TL 774 L (2021). Diluted for direct use.

VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-510214

Coolant G13 concentrate



Modern ethylene glycol-based coolant containing organic corrosion inhibitors, including silicates. It protects the cooling system of the motor vehicle against frost and corrosion all year round. Guarantees very good heat transfer. Particularly suitable for all-aluminium engines. Meets BS 6580 (2010), ASTM D 3306, SAE J 1034, Mercedes Benz325.5, MAN324 Si-OAT, VW TL 774 type J. The product is concentrated and diluted according to the instructions before use.

VOLUME: 1 l
PCS IN A CARTON: 12
CODE: CY-5877900

VOLUME: 25 l
PCS IN A CARTON: 1
CODE: CY-510979

VOLUME: 60 l
PCS IN A CARTON: 1
CODE: CY-510962

VOLUME: 200 l
PCS IN A CARTON: 1
CODE: CY-879829



IT'S EASY.

ACCESORIES



ACCESORIES

Fuel Can



Plastic can designed for fuels. It is provided with a transparent side window to determine the quantity of fuel in the can.

VOLUME: 5 l
PCS IN A CARTON: 12
CODE: CY-87906

VOLUME: 10 l
PCS IN A CARTON: 7
CODE: CY-87907

VOLUME: 20 l
PCS IN A CARTON: 12
CODE: CY-87908

First-aid Kit Plastic Box



First aid kit in a plastic closable box, size I. Box size 26 x 17 x 78 cm. A first aid kit is a part of the mandatory equipment of cars. The first-aid kit complies with Decree No. 341/2002 Coll., as amended by Decree No. 216/2010 Coll., Decree 182/2011 Coll., and Decree No. 341/2014 Coll., Annex No. 12 of the Ministry of Transport of the Czech Republic.

PCS IN A CARTON: 10
CODE: CY-50157

First-aid Kit Pillow



First aid kit in a textile lockable bag, size I. A first aid kit is a part of the mandatory equipment of cars. The first-aid kit complies with Decree No. 341/2002 Coll., as amended by Decree No. 216/2010 Coll., Decree 182/2011 Coll., and Decree No. 341/2014 Coll., Annex No. 12 of the Ministry of Transport of the Czech Republic.

PCS IN A CARTON: 20
CODE: CY-50158

Gloves size 10



It serves as hand protection against contamination and protection in the working environment when working in dry conditions with minor mechanical hazards (abrasion, soiling...). Use gloves on clean and dry hands. Requirements according to EN 338: Gripping ability - performance class: 5.

PCS IN A CARTON: 120
CODE: CY-504824

Winter gloves size 11



These gloves are simple personal work equipment designed to protect against only minimal risks, the consequences of which can be anticipated by the user in time - minor mechanical action, the effects of which are superficial. Weathering which is neither exceptional nor extreme in nature. They are not suitable for welding or handling highly aggressive chemicals, sharp or hot objects with a temperature higher than 50 °C. Protect gloves from radiant heat and from the effects of aggressive chemicals. They are not resistant to getting wet. Requirements according to EN 420: Gripping ability - performance class: 2.

PCS IN A CARTON: 60
CODE: CY-504831-1

Gloves size XL/10



Seamless gloves made of soft polyester knit. Palm and fingers coated with sandblasted nitrile for better grip. Recommended applications: logistics, storage, construction, hobby, working with slippery objects, automotive, municipal services, garden, assembly and packaging of small parts. Meets the EN 388 standard against mechanical risks and EN 420 protective gloves. CAT. II – medium risks.

PCS IN A CARTON: 120
CODE: CY-512409

Alcohol Test



It is used for one-time indicative detection of alcohol in exhaled air.

PCS IN A CARTON: 120
CODE: CY-877832

Ice scraper



Wooden handle, practical when using, durable material.

PCS IN A CARTON: 25
CODE: CY-506323

Sticker speed 80 km



Sticker speed 80 km, diameter 15 cm.

PCS IN A CARTON: 50
CODE: CY-509188

Sticker speed 90 km



Sticker speed 90 km, diameter 15 cm.

PCS IN A CARTON: 50
CODE: CY-509195

Sticker speed 100 km



Sticker speed 100 km, diameter 15 cm.

PCS IN A CARTON: 50
CODE: CY-509201

Sticker Beginner



Sticker with the motif of a beginner driver.

PCS IN A CARTON: 50
CODE: CY-509218

Sticker Baby on board



Sticker Baby on board

PCS IN A CARTON: 50
CODE: CY-509225

Standardized CZ sticker



Standardized CZ sticker


PCS IN A CARTON: 50
CODE: CY-509256


Towing rope 2.6t PAD





Car towing rope for passenger cars up to a total weight of 2600 kg.


PCS IN A CARTON: 50
CODE: CY-509751


Bulbs 12V		VOLUME:	OF PCS IN A CARTON:	CODE:
	Bulbs 12V 21W P21W BA15s	1	10/1000	CY-87861
	Bulbs 12V 21W PY21W orange BAU15s	1	10/1000	CY-87862
	Bulbs 12V 21/5W P21/5W BAY15d	1	10/1000	CY-87864
	Bulbs 12V 5W R5W BA15s	1	10/2000	CY-87866
	Bulbs 12V 10W R10W BA15s	1	10/2000	CY-87868
	Bulbs 12V 4W T4W BA9s	1	10/5000	CY-87870
	Bulbs 12V 5W T10 W5W all-glass	1	10/5000	CY-87871
	Bulbs 12V 1.2W W1.2W all-glass	1	10/5000	CY-87873
	Bulbs 12V 5W C5W soffit	1	10/5000	CY-87874
	Bulbs 12V 10W C10W soffit	1	10/5000	CY-87876


Bulbs 12V - Blister		VOLUME:	OF PCS IN A CARTON:	CODE:
	Bulbs 12V 1.2W W1.2W all-glass 2 pcs - Blister	2	10/100	CY-50128
	Bulbs 12V 10W C10W soffit 2 pcs - Blister	2	10/100	CY-50129
	Bulbs 12V 10W R10W BA15s 2 pcs - Blister	2	10/100	CY-50130
	Bulbs 12V 21/5W P21/5W BAY15d 2 pcs - Blister	2	10/100	CY-50131
	Bulbs 12V 21W P21W BA15s 2 pcs - Blister	2	10/100	CY-50132
	Bulbs 12V 21W PY21W orange BAU15s 2 pcs	2	10/100	CY-50133
	Bulbs 12V 5W C5W soffit 2 pcs - Blister	2	10/100	CY-50134
	Bulbs 12V 5W R5W BA15s 2 pcs - Blister	2	10/100	CY-50135
	Bulbs 12V 5W T10 W5W all-glass 2 pcs - Blister	2	10/100	CY-50136


Halogen Bulbs 12V		VOLUME:	OF PCS IN A CARTON:	CODE:
	Bulbs 12V H1 55W	1	1000	CY-87853
	Bulbs 12V H3 55W	1	1000	CY-87890
	Bulbs 12V H4 60/55W	1	250	CY-87856
	Bulbs 12V H7 55W	1	500	CY-87858

Halogen Bulbs 12V - Blister		VOLUME:	OF PCS IN A CARTON:	CODE:
	Bulbs 12V H1 55W - Blister	1	10/100	CY-50137
	Bulbs 12V H3 55W - Blister	1	10/100	CY-50138
	Bulbs 12V H4 60/55W - Blister	1	10/100	CY-50139
	Bulbs 12V H7 55W - Blister	1	10/100	CY-50140

Bulbs 12V SMD LED - Blister		VOLUME:	OF PCS IN A CARTON:	CODE:
	Bulbs 12V LED 5 SMD T10 CAN-BUS ready white	1	200	CY-50159
	Bulbs 12V LED 9 SMD T10 CAN-BUS ready white	1	200	CY-50160
	Bulbs 12V LED 2 SMD suf. SV8.5 CAN-BUS ready white	1	200	CY-50161
	Bulbs 12V LED 3 SMD suf. SV8.5 CAN-BUS ready white	1	200	CY-50162
	Bulbs 12V LED 19 SMD Ba15S CAN-BUS ready white	1	200	CY-50163
	Bulbs 12V LED 4 SMD Ba15S CAN-BUS ready white	1	200	CY-50164

Bulbs 24 V		VOLUME:	OF PCS IN A CARTON:	CODE:
	Bulbs 24V 21W P21W BA15s	1	10/1000	CY-87863
	Bulbs 24V 21/5W P21/5W BAY15d	1	10/1000	CY-87865
	Bulbs 24V 5W R5W BA15s	1	10/2000	CY-87867
	Bulbs 24V 10W R10W BA15s	1	10/2000	CY-87869
	Bulbs 24V 5W T10 W5W all-glass	1	10/5000	CY-87872
	Bulbs 24V 5W C5W soffit 11x35	1	10/5000	CY-87875
	Bulbs 24V 21W PY21W orange BAU15S	1	10/100	CY-50216

Halogen Bulbs 24V		VOLUME:	OF PCS IN A CARTON:	CODE:
	Bulbs 24V H1 70W	1	1000	CY-87854
	Bulbs 24V H4 75/70W	1	250	CY-87857
	Bulbs 24V H7 70W	1	500	CY-87859

Service Box Bulb 12 V		VOLUME:	OF PCS IN A CARTON:	CODE:
	Service Box Bulb 12V H4	1	100	CY-87877
	Service Box Bulb 12V H7	1	100	CY-87878



IT'S EASY.

METAL WORKING FLUIDS



METAL WORKING FLUIDS

WATER-MISCIBLE MACHINING FLUIDS

Name of a product	Characteristics	Application	Content mineral oils (%)	Lubricity
COYOTE WS 15 NF	<p>Semi-synthetic machining fluid, suitable for lower and medium-duty machining with a low content of mineral oils. Product without secondary amines and boric acid. The liquid forms an opalescent microemulsion that has excellent anti-corrosion properties in the entire recommended range of water hardness. The product has excellent cooling, wetting and rinsing capabilities and is excellent for grinding and light chipping operations.</p> <p>VOLUME: 20 l CODE: CY-513123 VOLUME: 200 l CODE: CY-513147</p>	<p>Materials: steel, cast iron</p> <p>Water hardness range: 6 - 60 °dH</p> <p>Recommended concentration: Chip machining 5 - 15 % Grinding 5 - 6 %</p>	15	*
COYOTE WS 25 NF	<p>Semi-synthetic machining fluid, suitable for medium-duty machining. Product without secondary amines and boric acid. The liquid forms a microemulsion that has excellent anti-corrosion properties in the entire recommended range of water hardness. The product has excellent cooling, wetting and rinsing capabilities and is excellent for grinding operations and general chip machining.</p> <p>VOLUME: 20 l CODE: CY-513134 VOLUME: 200 l CODE: CY-512553</p>	<p>Materials: steel, cast iron</p> <p>Water hardness range: 10 - 60 °dH</p> <p>Recommended concentration: Chip machining 5 - 15 % Grinding 5 - 6 %</p>	25	**
COYOTE WS 40 NB	<p>Semi-synthetic machining fluid, suitable for medium and higher machining demands. Product without bactericides, secondary amines and boric acid. The liquid forms a finely dispersed milky emulsion that excels in stability and longevity. The product has excellent lubricating, cooling, wetting and rinsing properties and is excellent for both chipping and grinding operations due to its excellent filterability.</p> <p>VOLUME: 20 l CODE: CY-512560 VOLUME: 200 l CODE: CY-512577</p>	<p>Materials: steel, cast iron, Al alloys, Cu alloys</p> <p>Water hardness range: 2- 60 °dH</p> <p>Recommended concentration: Chip machining 5 - 15 % Grinding 5 - 7 %</p>	40	***
COYOTE WS 46 NB	<p>Semi-synthetic machining fluid containing esters and EP additives, suitable for demanding machining. Product without bactericides, secondary amines and boric acid. The liquid forms a finely dispersed milky emulsion that excels in excellent lubricity, stability and longevity. The product has excellent lubricating, cooling, wetting and rinsing properties and is excellent for both chipping and grinding operations due to its excellent filterability. An ideal option, for example, for a wide range of tool production.</p> <p>VOLUME: 20 l CODE: CY-512584 VOLUME: 200 l CODE: CY-512591</p>	<p>Materials: steel, nerezová steel, litina, Al alloys, Cu alloys, titanium</p> <p>Water hardness range: 2 -60 °dH</p> <p>Recommended concentration: Chip machining 5 - 15 % Grinding 5 - 7 %</p>	46	****

Name of a product	Characteristics	Application	Content mineral oils (%)	Lubricity
COYOTE WS 70 NF	Mineral machining fluid suitable for medium-duty machining. Product without secondary amines and boric acid. The liquid forms a milky emulsion that excels in excellent lubricity, stability and universal applicability. The product can also be used for less demanding operations of pressing and forming moldings. VOLUME: 20 l CODE: CY-512607 VOLUME: 200 l CODE: CY-512614	Materials: anticorro, steel, cast iron, partially Al and Cu alloys Water hardness range: 5 - 25 °dH Recommended concentration: Chip machining 5 - 10 % Grinding 4 - 5 %	70	***
COYOTE WS 078 NB	Synthetic machining fluid suitable for demanding machining. Product without bactericides, secondary amines and boric acid. The liquid forms a transparent solution that excels in excellent lubricity, stability and extremely long service life. It perfectly separates liquids from dripping oils and thus still has stable properties. The product also has excellent wetting and rinsing capabilities that minimize fluid consumption by approximately 40% compared to conventional fluids and is excellent for both chipping and grinding operations. VOLUME: 20 l CODE: CY-512621 VOLUME: 200 l CODE: CY-512638	Materials: steel, stainless steel, Al alloys, Cu alloys, titanium, Inconel Water hardness range: 0 - 10 °dH Recommended concentration: Chip machining 5 - 15 % Grinding 5 - 7 %	0	****
COYOTE WS 098 NB	Synthetic machining fluid, suitable for medium-duty machining. Product without bactericides, secondary amines and boric acid. The liquid forms a transparent solution that stands out for its good rinsing and cleaning ability. The product has very good anti-corrosion properties, is very stable and is developed for grinding operations with the exception of centerless technology. VOLUME: 20 l CODE: CY-512645 VOLUME: 200 l CODE: CY-512652	Materials: steel, stainless steel, cast iron, titanium, glass, ceramic Water hardness range: 2 - 20 °dH Recommended concentration: Grinding 3 - 6 %	0	*

WATER-IMMISCIBLE MACHINING FLUIDS

Name of a product	Characteristics	Application	Viscosity at 40 °C (mm²/s) cca	Lubricity
COYOTE CO 5	Cutting oil based on mineral oils, suitable for medium-duty machining, containing additives to reduce the formation of oil mist and anti-corrosion additives. The product is suitable for finishing grinding operations, honing, and also for chip machining of aluminum alloys. The product is also intended for the lubrication of high-speed spindles with sliding bearings. VOLUME: 20 l CODE: CY-512669 VOLUME: 200 l CODE: CY-512676	Materials: steel, cast iron, Al alloys, Cu alloys	5	*

Name of a product	Characteristics	Application	Viscosity at 40 °C (mm²/s) cca	Lubricity
COYOTE CO 9	Cutting oil based on mineral oils, suitable for medium-duty machining, containing additives to reduce the formation of oil mist and anti-corrosion additives. The product is suitable for finishing grinding and honing operations. VOLUME: 20 l CODE: CY-512683 VOLUME: 200 l CODE: CY-512690	Materials: steel, cast iron, Al alloys, Cu alloys	9	**
COYOTE CO 12	Cutting oil based on mineral oils, suitable for medium-duty machining, containing additives to reduce the formation of oil mist and anti-corrosion additives. The product is suitable for finishing grinding operations and light chipping. VOLUME: 20 l CODE: CY-512706 VOLUME: 200 l CODE: CY-512713	Materials: steel, cast iron, Al alloys, Cu alloys	12	**
COYOTE CO 18	Cutting oil based on mineral oils, suitable for medium-duty machining, containing additives to reduce the formation of oil mist and anti-corrosion additives. The product is suitable for finishing grinding and chipping operations. VOLUME: 20 l CODE: CY-512720 VOLUME: 200 l CODE: CY-512737	Materials: steel, cast iron, Al alloys, Cu alloys	18	**
COYOTE CO 25	Cutting oil based on mineral oils, suitable for medium-duty machining, containing additives to reduce the formation of oil mist and anti-corrosion additives. The product is suitable for chip machining. VOLUME: 20 l CODE: CY-512744 VOLUME: 200 l CODE: CY-512751	Materials: steel, cast iron, Al alloys, Cu alloys	25	**
COYOTE CMF 32	Cutting oil based on mineral oils, suitable for medium-duty machining, containing additives to reduce the formation of oil mist and anti-corrosion additives. The product is particularly suitable for chip machining and at the same time meets the specification for HLP hydraulic oil ISO VG 32 according to DIN 51 524 part 2. VOLUME: 20 l CODE: CY-512768 VOLUME: 200 l CODE: CY-512775	Materials: steel, cast iron, Al alloys, Cu alloys	32	*
COYOTE CMF 46	Cutting oil based on mineral oils, suitable for medium-duty machining, containing additives to reduce the formation of oil mist and anti-corrosion additives. The product is particularly suitable for chip machining and at the same time meets the specification for HLP hydraulic oil ISO VG 46 according to DIN 51 524 part 2. VOLUME: 20 l CODE: CY-512782 VOLUME: 200 l CODE: CY-512799	Materials: steel, cast iron, Al alloys, Cu alloys	46	*

Name of a product	Characteristics	Application	Viscosity at 40 °C (mm²/s) cca	Lubricity
COYOTE COA 10	Cutting oil based on low-aromatic mineral oils, suitable for high-demand machining, containing effective EP additives, additives to reduce the formation of oil mist and anti-corrosion additives. With its properties, it creates an optimal cutting environment with an effective limitation of the build-up. The product is particularly suitable for grinding and chip machining. VOLUME: 20 l CODE: CY-512805 VOLUME: 200 l CODE: CY-512812	Materials: alloy steel, stainless steel	10	***
COYOTE COA 15	Cutting oil based on low-aromatic mineral oils, suitable for high-demand machining, containing effective EP additives, additives to reduce the formation of oil mist and anti-corrosion additives. With its properties, it creates an optimal cutting environment with an effective limitation of the build-up. The product is particularly suitable for chip machining and deep drilling. VOLUME: 20 l CODE: CY-512829 VOLUME: 200 l CODE: CY-512836	Materials: alloy steel, stainless steel	15	***
COYOTE COA 22	Cutting oil based on low-aromatic mineral oils, suitable for high-demand machining, containing effective EP additives, additives to reduce the formation of oil mist and anti-corrosion additives. With its properties, it creates an optimal cutting environment with an effective limitation of the build-up. The product is particularly suitable for chip machining and deep drilling. VOLUME: 20 l CODE: CY-512843 VOLUME: 200 l CODE: CY-512850	Materials: alloy steel, stainless steel	22	***
COYOTE COA 26	Cutting oil based on low-aromatic mineral oils, suitable for high-demand machining, containing effective EP additives, additives to reduce the formation of oil mist and anti-corrosion additives. With its properties, it creates an optimal cutting environment with an effective limitation of the build-up. The product is particularly suitable for chip machining. VOLUME: 20 l CODE: CY-512867 VOLUME: 200 l CODE: CY-512874	Materials: alloy steel, stainless steel	26	***
COYOTE COA 35	Cutting oil based on low-aromatic mineral oils, suitable for high-demand machining, containing effective EP additives, native fat additives, additives to reduce the formation of oil mist and anti-corrosion additives. With its properties, it creates an optimal cutting environment with an effective limitation of the build-up. The product is particularly suitable for deep drilling, stretching and shaving operations. VOLUME: 20 l CODE: CY-512881 VOLUME: 200 l CODE: CY-512898	Materials: alloy steel, stainless steel	35	***

Name of a product	Characteristics	Application	Viscosity at 40 °C (mm²/s) cca	Lubricity
COYOTE GO 7 GTL	Grinding oil based on special GTL raffinates with a high viscosity index, suitable for high machining demands, containing effective EP additives, additives to reduce the formation of oil mist and anti-corrosion additives. Thanks to the special modern GTL technology, their properties are comparable to oils of the PAO category. The product is particularly suitable for demanding cemented carbide grinding operations. The oil is inhibited against the release of cobalt. VOLUME: 20 l CODE: CY-512904 VOLUME: 200 l CODE: CY-512911	Materials: cemented carbides, steel, cast iron, titanium, Al alloys, Cu alloys	7	**

ANTI-CORROSION AGENTS

Name of a product	Characteristics	Application	Viscosity at 40 °C (mm²/s) cca	corrosion protection (indoor)
COYOTE ACP 1 EV	Evaporative preservative, designed to protect products against corrosion. The product displaces water on the surface of the preserved material and reliably protects it against external corrosion. It is used for medium-term protection. The product creates a very thin vaseline protective film with a thickness of 1.5 µm on the material. VOLUME: 20 l CODE: CY-512928 VOLUME: 200 l CODE: CY-512935	dive, spray, manual application	1	9 - 12 months
COYOTE ACP 2 EV	Evaporative preservative, designed to protect products against corrosion. The product displaces water on the surface of the preserved material and reliably protects it against external corrosion. It is used for medium-term protection. The product creates a very thin protective oil film of 1.4 µm on the material. VOLUME: 20 l CODE: CY-512942 VOLUME: 200 l CODE: CY-512959	dive, spray, manual application	2	6 - 9 months
COYOTE ACP 16	Preservative oil on a mineral basis, designed to protect products against corrosion. The product is odorless and contains no solvents. It is used for medium-term protection. The product creates an oil protective film with a thickness of 10 µm on the material. VOLUME: 20 l CODE: CY-512966 VOLUME: 200 l CODE: CY-512973	dive, spray, manual application	16	6 - 9 months
COYOTE ACP 40	Preservative oil on a mineral basis, designed to protect products against corrosion. The product is odorless and contains no solvents. It is used for long-term protection. The product creates an oil protective film with a thickness of 17 µm on the material. VOLUME: 20 l CODE: CY-512522 VOLUME: 200 l CODE: CY-512539	dive, spray, manual application	40	18 - 24 months

DEGREASING AGENTS

Name of a product	Characteristics	Application	Flash point (°C)	Product type:
COYOTE CLEAN EV	Degreaser based on synthetic hydrocarbons, non-toxic, free of aromatics, benzene, sulfur and chlorine. Suitable for industrial, hand washing and cold decontamination of metal parts and machine parts. It is used very often as a filling for washing tables and ultrasonic washing machines to remove operational dirt, petroleum oils, lubricating greases, carbon and the like. It serves as a substitute for chlorinated hydrocarbons and gasoline. Flammable hazard class 3.	dive, spray, manual application	64	immiscible with water
	VOLUME: 20 l CODE: CY-513000 VOLUME: 200 l CODE: CY-513017			
COYOTE CLEAN AQ	Universal alkaline water-based degreaser for cold application. The product is suitable for cleaning machines, floors and high-pressure cleaning. It reliably removes a high level of dirt.	Recommended concentration: hand wash 1 - 10 % high pressure wash 3 - 5 %	non flammable	water miscible
	VOLUME: 20 l CODE: CY-513024 VOLUME: 200 l CODE: CY-513031			

AutoMax

Autochemie

AutoMax Group s.r.o.

K Hájům 1233/2, 155 00 Praha 5

IČ: 43873588, DIČ: CZ43873588

Firma je zaregistrována u Městského soudu v Praze,
Obchodní rejstřík odd. C, vložka 5548.

E-mail: info.cz@automax-group.com

Tel: +420 272 700 530

www.automax-group.com



www.facebook.com/coyote.cz

www.instagram.com/coyote.cz